

STANDARD STORAGE TANKS

Catalog No.		Dimensions			Capacity (ACTUAL gallons +/- 3)	SQ. FT.	Openings		Manway See Note
		OD In.	Shell In.	OAL(1) In.			"B" Rel. VA	"G" Drain	
WS-24-3	(2)	24	36	51	91	28	1"	1"	N/A
WS-24-4	(2)	24	48	63	114	31	1"	1"	N/A
WS-24-5	(2)	24	60	75	137	40	1"	1"	N/A
WS-24-6	(2)	24	72	87	159	46	1"	1"	N/A
WS-24-7	(2)	24	84	99	182	53	1"	1"	N/A
WS-24-8	(2)	24	96	111	205	59	1"	1"	N/A
WS-30-4	(2)	30	48	66	185	45	1"	1"	N/A
WS-30-5	(2)	30	60	78	220	53	1"	1"	N/A
WS-30-6	(2)	30	72	90	256	60	1"	1"	N/A
WS-30-7	(2)	30	84	102	292	68	1"	1"	N/A
WS-30-8	(2)	30	96	114	328	75	1"	1"	N/A
WS-30-9	(2)	30	108	126	364	82	1"	1"	N/A
WS-36-4NM		36	48	68	271	54	1"	1-1/2"	None
WS-36-5NM		36	60	80	322	63	1"	1-1/2"	None
WS-36-6NM		36	72	92	374	73	1"	1-1/2"	None
WS-36-7NM		36	84	104	426	82	1"	1-1/2"	None
WS-36-8NM		36	96	116	478	92	1"	1-1/2"	None
WS-36-9NM		36	108	128	530	101	1"	1-1/2"	None
WS-36-10NM		36	120	140	581	110	1"	1-1/2"	None
WS-36-4		36	48	68	271	54	1"	1-1/2"	Lined Only
WS-36-5		36	60	80	322	63	1"	1-1/2"	Lined Only
WS-36-6		36	72	92	374	73	1"	1-1/2"	Lined Only
WS-36-7		36	84	104	426	82	1"	1-1/2"	Lined Only
WS-36-8		36	96	116	478	92	1"	1-1/2"	Lined Only
WS-36-9		36	108	128	530	101	1"	1-1/2"	Lined Only
WS-36-10		36	120	140	581	110	1"	1-1/2"	Lined Only
WS-42-4		42	48	70	380	67	1"	1-1/2"	All
WS-42-5		42	60	82	451	78	1"	1-1/2"	All
WS-42-6		42	72	94	522	89	1"	1-1/2"	All
WS-42-7		42	84	106	593	100	1"	1-1/2"	All
WS-42-8		42	96	118	663	110	1"	1-1/2"	All
WS-42-9		42	108	130	734	121	1"	1-1/2"	All
WS-42-10		42	120	142	805	132	1"	1-1/2"	All
WS-42-11		42	132	154	875	148	1"	1-1/2"	All
WS-42-12		42	144	166	946	154	1"	1-1/2"	All
WS-42-13		42	156	178	1017	170	1"	1-1/2"	All
WS-48-4		48	48	74	508	80	1-1/2"	2"	All
WS-48-5		48	60	86	601	93	1-1/2"	2"	All
WS-48-6		48	72	98	693	105	1-1/2"	2"	All
WS-48-7		48	84	110	785	118	1-1/2"	2"	All
WS-48-8		48	96	122	877	130	1-1/2"	2"	All
WS-48-9		48	108	134	969	142	1-1/2"	2"	All
WS-48-10		48	120	146	1061	155	1-1/2"	2"	All
WS-48-11		48	132	158	1153	167	1-1/2"	2"	All
WS-48-12		48	144	170	1245	180	1-1/2"	2"	All
WS-48-13		48	156	182	1337	192	1-1/2"	2"	All
WS-48-14		48	168	194	1429	205	1-1/2"	2"	All
WS-48-15		48	180	206	1521	217	1-1/2"	2"	All

(1)Overall length may vary depending on the type of head used and does not include supports

(2)Also available as galvanized. Consult factory.

NOTE: ALL LINED TANKS HAVE A 12" X 16" MANWAY. ALL UNLINED TANKS 42" OD AND OVER HAVE A 12" X 16" MANWAY

STANDARD STORAGE TANKS

Catalog No.	Dimensions			Capacity (ACTUAL gallons +/- 3)	SQ. FT.	Openings		Manway See Note
	OD In.	Shell In.	OAL(1) In.			"B" Relief	"G" Drain	
WS-54-4	54	48	77	659	94	1-1/2"	2"	All
WS-54-5	54	60	89	775	108	1-1/2"	2"	All
WS-54-6	54	72	101	892	122	1-1/2"	2"	All
WS-54-7	54	84	113	1009	136	1-1/2"	2"	All
WS-54-8	54	96	125	1126	150	1-1/2"	2"	All
WS-54-9	54	108	137	1243	164	1-1/2"	2"	All
WS-54-10	54	120	149	1359	178	1-1/2"	2"	All
WS-54-11	54	132	161	1476	192	1-1/2"	2"	All
WS-54-12	54	144	173	1593	206	1-1/2"	2"	All
WS-54-13	54	156	185	1710	220	1-1/2"	2"	All
WS-54-14	54	168	197	1827	234	1-1/2"	2"	All
WS-54-15	54	180	209	1943	248	1-1/2"	2"	All
WS-54-16	54	192	221	2060	262	1-1/2"	2"	All
WS-54-17	54	204	233	2177	276	1-1/2"	2"	All
WS-60-4	60	48	78	831	114	1-1/2"	2"	All
WS-60-5	60	60	90	975	130	1-1/2"	2"	All
WS-60-6	60	72	102	1119	146	1-1/2"	2"	All
WS-60-7	60	84	114	1263	162	1-1/2"	2"	All
WS-60-8	60	96	126	1407	177	1-1/2"	2"	All
WS-60-9	60	108	138	1551	193	1-1/2"	2"	All
WS-60-10	60	120	150	1694	208	1-1/2"	2"	All
WS-60-11	60	132	162	1838	224	1-1/2"	2"	All
WS-60-12	60	144	174	1982	240	1-1/2"	2"	All
WS-60-13	60	156	186	2126	256	1-1/2"	2"	All
WS-60-14	60	168	198	2270	272	1-1/2"	2"	All
WS-60-15	60	180	210	2414	287	1-1/2"	2"	All
WS-60-16	60	192	222	2558	302	1-1/2"	2"	All
WS-60-17	60	204	234	2701	318	1-1/2"	2"	All
WS-60-18	60	216	246	2845	334	1-1/2"	2"	All
WS-60-19	60	228	258	2989	350	1-1/2"	2"	All
WS-60-20	60	240	270	3133	366	1-1/2"	2"	All
WS-60-21	60	252	282	3277	381	1-1/2"	2"	All
WS-66-4	66	48	82	1033	135	1-1/2"	2"	All
WS-66-5	66	60	94	1208	152	1-1/2"	2"	All
WS-66-6	66	72	106	1382	169	1-1/2"	2"	All
WS-66-7	66	84	118	1557	186	1-1/2"	2"	All
WS-66-8	66	96	130	1731	203	1-1/2"	2"	All
WS-66-9	66	108	142	1905	221	1-1/2"	2"	All
WS-66-10	66	120	154	2080	237	1-1/2"	2"	All
WS-66-11	66	132	166	2254	254	1-1/2"	2"	All
WS-66-12	66	144	178	2428	271	1-1/2"	2"	All
WS-66-13	66	156	190	2603	289	1-1/2"	2"	All
WS-66-14	66	168	202	2777	306	1-1/2"	2"	All
WS-66-15	66	180	214	2952	323	1-1/2"	2"	All
WS-66-16	66	192	226	3126	340	1-1/2"	2"	All
WS-66-17	66	204	238	3300	357	1-1/2"	2"	All
WS-66-18	66	216	250	3475	374	1-1/2"	2"	All
WS-66-19	66	228	262	3649	391	1-1/2"	2"	All
WS-66-20	66	240	274	3824	409	1-1/2"	2"	All
WS-66-21	66	252	286	3998	426	1-1/2"	2"	All

(1)Overall length may vary depending on the type of head used and does not include supports

(2)Also available as galvanized. Consult factory.

NOTE: ALL LINED TANKS HAVE A 12" X 16" MANWAY. ALL UNLINED TANKS 42" OD AND OVER HAVE A 12" X 16" MANWAY

STANDARD STORAGE TANKS

Catalog No.	Dimensions			Capacity (ACTUAL gallons +/- 3)	SQ. FT.	Openings		Manway See Note
	OD In.	Shell In.	OAL In.			"B" Rel. VA	"G" Drain	
WS-72-5	72	60	96	1469	172	1-1/2"	2"	All
WS-72-6	72	72	108	1677	191	1-1/2"	2"	All
WS-72-7	72	84	120	1885	210	1-1/2"	2"	All
WS-72-8	72	96	132	2093	229	1-1/2"	2"	All
WS-72-9	72	108	144	2301	248	1-1/2"	2"	All
WS-72-10	72	120	156	2509	267	1-1/2"	2"	All
WS-72-11	72	132	168	2717	286	1-1/2"	2"	All
WS-72-12	72	144	180	2924	304	1-1/2"	2"	All
WS-72-13	72	156	192	3132	323	1-1/2"	2"	All
WS-72-14	72	168	204	3340	342	1-1/2"	2"	All
WS-72-15	72	180	216	3548	360	1-1/2"	2"	All
WS-72-16	72	192	228	3756	379	1-1/2"	2"	All
WS-72-17	72	204	240	3964	398	1-1/2"	2"	All
WS-72-18	72	216	252	4172	417	1-1/2"	2"	All
WS-72-19	72	228	264	4380	438	1-1/2"	2"	All
WS-72-20	72	240	276	4587	457	1-1/2"	2"	All
WS-72-22	72	264	300	5003	495	1-1/2"	2"	All
WS-72-24	72	288	336	5211	514	1-1/2"	2"	All
WS-84-5	84	60	103	2082	208	1-1/2"	2"	All
WS-84-6	84	72	115	2366	230	1-1/2"	2"	All
WS-84-7	84	84	127	2649	252	1-1/2"	2"	All
WS-84-8	84	96	139	2933	274	1-1/2"	2"	All
WS-84-10	84	120	163	3500	318	1-1/2"	2"	All
WS-84-12	84	144	187	4068	362	1-1/2"	2"	All
WS-84-14	84	168	211	4635	406	1-1/2"	2"	All
WS-84-16	84	192	235	5202	450	1-1/2"	2"	All
WS-84-18	84	216	259	5769	494	1-1/2"	2"	All
WS-84-20	84	240	283	6337	538	1-1/2"	2"	All
WS-84-22	84	264	307	6904	582	1-1/2"	2"	All
WS-84-24	84	288	331	7471	626	1-1/2"	2"	All
WS-96-5	96	60	108	2833	250	1-1/2"	2"	All
WS-96-6	96	72	120	3203	275	1-1/2"	2"	All
WS-96-7	96	84	132	3573	300	1-1/2"	2"	All
WS-96-8	96	96	144	3944	325	1-1/2"	2"	All
WS-96-10	96	120	168	4684	375	1-1/2"	2"	All
WS-96-11	96	132	180	5054	400	1-1/2"	2"	All
WS-96-12	96	144	192	5425	425	1-1/2"	2"	All
WS-96-14	96	168	216	6165	475	1-1/2"	2"	All
WS-96-16	96	192	240	6905	525	1-1/2"	2"	All
WS-96-18	96	216	264	7646	575	1-1/2"	2"	All
WS-96-20	96	240	288	8386	625	1-1/2"	2"	All
WS-96-22	96	264	312	9127	675	1-1/2"	2"	All
WS-96-24	96	288	336	9,867	725	1-1/2"	2"	All
WS-96-32	96	384	432	12,829	925	1-1/2"	2"	All

(1)Overall length may vary depending on the type of head used and does not include support

(2)Also available as galvanized. Consult factory.

NOTE: ALL LINED TANKS HAVE A 12" X 16" MANWAY. ALL UNLINED TANKS 42" OD AND OVER HAVE A 12" X 16" MANWAY